

6030/6080 SERIES CARBON MONOXIDE DETECTORS

The 6030/6080 120V outlet plug-in is for single station use only. With an advanced new design, the 6030/6080 carbon monoxide alarm has a unique alarm action guide that fits conveniently and discreetly behind the unit. For easy access, the card with illustrated emergency instructions simply slides out from behind the unit. In addition, the 6030/6080 has a rotatable plug for flexible outlet.

SOURCES OF CARBON MONOXIDE: Carbon monoxide is a by-product of combustion. Common fuels include, but are not limited to: gasoline, natural gas, propane, butane, wood, heating oil, coal, charcoal, etc. Combustion occurs in all gas engines, furnaces, gas water and space heaters, boilers, gas stoves and ovens, gas/charcoal grills, etc.



ORDERING DATA

UNI-LINE ORDER NO.	SUPPLY VOLTAGE	DESCRIPTION
6030	120 VAC	120 VAC PLUG-IN CO ALARM
6080	120 VAC	120 VAC PLUG-IN CO ALARM (CANADA)

SPECIFICATIONS

Electrical rating	120 VAC, 60 Hz, 50mA max.
Operating temperature	40°F to 100°F
Humidity range	15% to 95% relative humidity
Case dimensions	5.1" x 3.3" x 1.7"
Gas detected	Carbon Monoxide (CO)
CO alarm level	10% or more COHb potential
Audible alarm	85 dB at 10 feet
UL Listing	6030 — UL 2034 6080 — ULC S531
Detection type	Biomimetic
Interconnect qty.	Single station
Product weight	7 oz.

6040/6090 SERIES CARBON MONOXIDE DETECTORS

The 6040/6090 120 VAC direct wire with battery back-up is for single or multiple station use. The 6040/6090 can operate independently or is interconnectable with up to 12 other Firex carbon monoxide alarms. Quick connect pigtail wiring and separate mounting brackets are included with these units to allow surface, junction box or octagon box installation.



ORDERING DATA

UNI-LINE ORDER NO.	SUPPLY VOLTAGE	DESCRIPTION
6040	120 VAC	120 VAC DIRECT WIRE W/ 9V BATTERY BACK-UP
6090	120 VAC	120 VAC DIRECT WIRE W/ 9V BATTERY BACK-UP (CANADA)

SPECIFICATIONS

Electrical rating	120 VAC, 60 Hz, 50mA max., 9 volt battery
Operating temperature	40°F to 100°F
Humidity range	15% to 95% relative humidity
Case dimensions	4.75" x 4.75" x 1.65"
Gas detected	Carbon Monoxide (CO)
CO alarm level	10% or more COHb potential
Audible alarm	85 dB at 10 feet
Battery check	Flashing red LED
Malfunctioning alarm	Yellow LED
Power ON in standby	Green LED
UL Listing	6040 — UL 2034 6090 — ULC S531
Detection type	Biomimetic
Interconnect qty.	Up to 12 identical units
Product weight	17 oz.